


DOUBLE HUNG WINDOWS

Multiple assemblies

All these units are available in 2-wide and 3-wide assemblies (calculate the total width by multiplying the width of a module by 2 or 3).


Determine rough openings as indicated below.



MULTIPLE ASSEMBLY ROUGH OPENING	
Width	Height
Add frame width PLUS 1"	Add frame height PLUS ½"

Cottage-Style Units

Double hung units are available in Cottage-Style configurations. Please contact your local Lepage representative for restrictions and lite cut configurations.



WH11

R.O. (mm)	22 5/8" (575)	26 5/8" (676)	30 5/8" (778)	32 5/8" (829)	34 5/8" (879)
F.S. (mm)	21 5/8" (549)	25 5/8" (651)	29 5/8" (752)	31 5/8" (803)	33 5/8" (854)
V.G. (mm)	14 3/4" (376)	18 3/4" (478)	22 3/4" (579)	24 3/4" (630)	26 3/4" (681)

R.O. (mm)	41 3/8" (1051)	45 3/8" (1152)	49 3/8" (1254)	53 3/8" (1356)	57 3/8" (1457)	61 3/8" (1559)	65 3/8" (1661)	69 3/8" (1762)	73 3/8" (1864)	77 3/8" (1965)	81 3/8" (2067)	
F.S. (mm)	40 7/8" (1038)	44 7/8" (1241)	48 7/8" (1241)	52 7/8" (1343)	56 7/8" (1445)	60 7/8" (1546)	64 7/8" (1648)	68 7/8" (1749)	72 7/8" (1851)	76 7/8" (1953)	80 7/8" (2054)	
V.G. (mm)	13 3/8" (340)	17 3/8" (441)	19 3/8" (492)	21 3/8" (543)	23 3/8" (594)	25 3/8" (644)	27 3/8" (695)	29 3/8" (746)	31 3/8" (797)	33 3/8" (848)	35 3/8" (898)	
	1614	1616	1618	1620	1622	1624	1626	1628	1630	1632*	1634*	1636*
	2014	2016	2018	2020	2022	2024	2026*	2028*	2030*	2032*	2034*	2036*
	2414	2416	2418	2420	2422*	2424*	2426*	2428*	2430*	2432*	2434**	2436**
	2614	2616	2618	2620	2622*	2624*	2626*	2628*	2630*	2632**	2634**	2636**
	2814	2816	2818	2820*	2822*	2824*	2826*	2828*	2830**	2832**	2834**	2836**

* Please visit our web site for the energy performance of these products at www.lepageillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative. Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Meets Canadian EGRESS requirements
** Meets U.S. EGRESS requirements

DOUBLE HUNG WINDOWS

WH11

R.O. (mm)	36 5/8" (930)	38 5/8" (981)	42 5/8" (1083)	46 5/8" (1184)
F.S. (mm)	35 5/8" (905)	37 5/8" (956)	41 5/8" (1057)	45 5/8" (1159)
V.G. (mm)	28 3/4" (732)	30 3/4" (783)	34 3/4" (884)	38 3/4" (986)

R.O. (mm)	41 3/8" (1051)	45 3/8" (1152)	49 3/8" (1254)	53 3/8" (1356)	57 3/8" (1457)	61 3/8" (1559)	65 3/8" (1661)	69 3/8" (1762)	73 3/8" (1864)	77 3/8" (1965)	81 3/8" (2067)	
F.S. (mm)	40 7/8" (1038)	44 7/8" (1241)	48 7/8" (1241)	52 7/8" (1343)	56 7/8" (1445)	60 7/8" (1546)	64 7/8" (1648)	68 7/8" (1749)	72 7/8" (1851)	76 7/8" (1953)	80 7/8" (2054)	
V.G. (mm)	15 3/8" (390)	17 3/8" (441)	19 3/8" (492)	21 3/8" (543)	23 3/8" (594)	25 3/8" (644)	27 3/8" (695)	29 3/8" (746)	31 3/8" (797)	33 3/8" (848)	35 3/8" (898)	
	3014	3016	3018*	3020*	3022*	3024*	3026*	3028**	3030**	3032**	3034**	3036**
	3214	3216	3218*	3220*	3222*	3224*	3226**	3228**	3230**	3232**	3234**	3236**
	3614	3616*	3618*	3620*	3622*	3624*	3626**	3628**	3630**	3632**		
	4014	4016*	4018*	4020*	4022*	4024*	4026**	4028**	4030**	4032**		

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local Lepage representative. Lite patterns shown are 7/8" (22) SDL. Lite patterns for 3/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Meets Canadian EGRESS requirements
** Meets U.S. EGRESS requirements

DOUBLE HUNG WINDOWS

WH2L

R.O. (mm)	59 7/8" (1521)	83 7/8" (2130)	95 7/8" (2435)	107 7/8" (2740)
F.S. (mm)	58 7/8" (1497)	82 7/8" (2106)	94 7/8" (2411)	106 7/8" (2716)
W.F. (mm)	21 5/8" (549)	29 3/8" (752)	33 3/8" (854)	37 5/8" (956)
V.G.F. (mm)	14 3/4" (376)	22 3/4" (579)	26 3/4" (681)	30 3/4" (783)
V.G.P. (mm)	30 1/2" (774)	46 1/2" (1181)	54 1/2" (1384)	62 1/2" (1587)

R.O. (mm)	81 3/8" (2067)	77 3/8" (1965)	73 3/8" (1864)	69 3/8" (1762)	65 3/8" (1661)	61 3/8" (1559)	57 3/8" (1457)	53 3/8" (1356)	49 3/8" (1254)	45 3/8" (1152)	41 3/8" (1051)	37 3/8" (949)
F.S. (mm)	80 7/8" (2054)	76 7/8" (1953)	72 7/8" (1851)	68 7/8" (1749)	64 7/8" (1648)	60 7/8" (1546)	56 7/8" (1445)	52 7/8" (1343)	48 7/8" (1241)	44 7/8" (1140)	40 7/8" (1038)	36 7/8" (937)
V.G.F. (mm)	35 3/8" (898)	33 3/8" (848)	31 3/8" (797)	29 3/8" (746)	27 3/8" (695)	25 3/8" (644)	23 3/8" (594)	21 3/8" (543)	19 3/8" (492)	17 3/8" (441)	15 3/8" (390)	13 3/8" (340)
V.G.P. (mm)	72 5/8" (1846)	68 5/8" (1744)	64 5/8" (1643)	60 5/8" (1541)	56 5/8" (1440)	52 5/8" (1338)	48 5/8" (1236)	44 5/8" (1135)	40 5/8" (1033)	36 5/8" (932)	32 5/8" (830)	28 5/8" (728)
	1636*	1634*	1632*	1630	1628	1626	1624	1622	1620	1618	1616	1614
	2436**	2434**	2432*	2430*	2428*	2426*	2424*	2422*	2420	2418	2416	2414
	2836**	2834**	2832**	2830**	2828*	2826*	2824*	2822*	2820*	2818	2816	2814
	3236**	3234**	3232**	3230**	3228**	3226*	3224*	3222*	3220*	3218*	3216	3214

* Please visit our web site for the energy performance of these products at www.lepageillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options. For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 3/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary. Grille configurations shown have been designed for grilles to align with flankers, therefore lite cuts are NOT equal. Equal lite cuts are available on request, but will NOT ALIGN with the grilles in the flankers.

Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.

R.O.: Rough Opening
 F.S.: Frame Size
 W.F.: Width of Flanker
 V.G.F.: Visible Glass of Flanker
 V.G.P.: Visible Glass of Picture Unit
 * Meets Canadian EGRESS requirements
 ** Meets U.S. EGRESS requirements

DOUBLE HUNG WINDOWS

WH3L

R.O. (mm)	81 1/2" (2070)	113 1/2" (2883)	129 1/2" (3289)	145 1/2" (3696)
F.S. (mm)	80 1/2" (2046)	112 1/2" (2859)	128 1/2" (3265)	144 1/2" (3672)
W.F. (mm)	21 5/8" (549)	29 5/8" (752)	33 5/8" (854)	37 5/8" (956)
V.G.F. (mm)	14 3/4" (376)	22 3/4" (579)	26 3/4" (681)	30 3/4" (783)
V.G.P. (mm)	30 1/2" (774)	46 1/2" (1181)	54 1/2" (1384)	62 1/2" (1587)

R.O. (mm)	81 3/8" (2067)	77 3/8" (1965)	73 3/8" (1864)	69 3/8" (1762)	65 3/8" (1661)	61 3/8" (1559)	57 3/8" (1457)	53 3/8" (1356)	49 3/8" (1254)	45 3/8" (1152)	41 3/8" (1051)	37 3/8" (949)
F.S. (mm)	80 7/8" (2054)	76 7/8" (1953)	72 7/8" (1851)	68 7/8" (1749)	64 7/8" (1648)	60 7/8" (1546)	56 7/8" (1445)	52 7/8" (1343)	48 7/8" (1241)	44 7/8" (1140)	40 7/8" (1038)	36 7/8" (937)
V.G.F. (mm)	35 3/8" (898)	33 3/8" (848)	31 3/8" (797)	29 3/8" (746)	27 3/8" (695)	25 3/8" (644)	23 3/8" (594)	21 3/8" (543)	19 3/8" (492)	17 3/8" (441)	15 3/8" (390)	13 3/8" (340)
V.G.P. (mm)	72 5/8" (1846)	68 5/8" (1744)	64 5/8" (1643)	60 5/8" (1541)	56 5/8" (1440)	52 5/8" (1338)	48 5/8" (1236)	44 5/8" (1135)	40 5/8" (1033)	36 5/8" (932)	32 5/8" (830)	28 5/8" (728)
	1636*	1634*	1632*	1630	1628	1626	1624	1622	1620	1618	1616	1614
	2436**	2434**	2432*	2430*	2428*	2426*	2424*	2422*	2420	2418	2416	2414
	2836**	2834**	2832**	2830**	2828*	2826*	2824*	2822*	2820*	2818	2816	2814
	3236**	3234**	3232**	3230**	3228**	3226**	3224*	3222*	3220*	3218*	3216	3214

R.O.: Rough Opening
F.S.: Frame Size
W.F.: Width of Flanker

V.G.F.: Visible Glass of Flanker
V.G.P.: Visible Glass of Picture Unit

* Meets Canadian EGRESS requirements
** Meets U.S. EGRESS requirements

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local LePage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/8" (31) SDL and other grilles may vary.

Grille configurations shown have been designed for grilles to align with flankers, therefore lite cuts are NOT equal. Equal lite cuts are available on request, but will NOT ALIGN with the grilles in the flankers.

Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.

DOUBLE HUNG WINDOWS - TRANSOMS

WHTT (to match standard double hungs)

R.O. (mm)	22 5/8" (575)	26 5/8" (676)	30 5/8" (778)	32 5/8" (829)	34 5/8" (879)	36 5/8" (930)	38 5/8" (981)	42 5/8" (1083)	46 5/8" (1184)
F.S. (mm)	21 5/8" (549)	25 5/8" (651)	29 5/8" (752)	31 5/8" (803)	33 5/8" (854)	35 5/8" (905)	37 5/8" (956)	41 5/8" (1057)	45 5/8" (1159)
V.G. (mm)	14 3/4" (376)	18 3/4" (478)	22 3/4" (579)	24 3/4" (630)	26 3/4" (681)	28 3/4" (732)	30 3/4" (783)	34 3/4" (884)	38 3/4" (986)

R.O. (mm)	12 1/2" (318)	16 1/2" (419)	20 1/2" (521)	26 5/8" (676)	30 5/8" (778)
F.S. (mm)	12" (305)	16" (406)	20" (508)	26 1/8" (665)	30 1/8" (767)
V.G. (mm)	5 1/4" (132)	9 1/4" (233)	13 1/4" (335)	19 3/8" (492)	23 3/8" (594)

1606	2006	2406	2606	2806	3006	3206	3606	4006
1610	2010	2410	2610	2810	3010	3210	3610	4010
1614	2014	2414	2614	2814	3014	3214	3614	4014
1620	2020	2420	2620	2820	3020	3220	3620	4020
1624	2024	2424	2624	2824	3024	3224	3624	4024

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

WHTP (to match standard picture units)

R.O. (mm)	38 1/4" (972)	54 1/4" (1378)	62 1/4" (1581)	70 1/4" (1784)
F.S. (mm)	37 1/4" (948)	53 1/4" (1354)	61 1/4" (1557)	69 1/4" (1760)
V.G. (mm)	30 1/2" (775)	46 1/2" (1181)	54 1/2" (1384)	62 1/2" (1587)

R.O. (mm)	12 1/2" (318)	16 1/2" (419)	20 1/2" (521)	26 5/8" (676)	30 5/8" (778)
F.S. (mm)	12" (305)	16" (406)	20" (508)	26 1/8" (665)	30 1/8" (767)
V.G. (mm)	5 1/4" (132)	9 1/4" (233)	13 1/4" (335)	19 3/8" (492)	23 3/8" (594)

3206	4806	5606	6406
3210	4810	5610	6410
3214	4814	5614	6414
3220	4820	5620	6420
3224	4824	5624	6424

R.O.: Rough Opening
F.S.: Frame Size
V.G.: Visible Glass

* Please visit our web site for the energy performance of these products at www.lepagemillwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.

For masonry openings, please contact your local Lepage representative.

Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.

DOUBLE HUNG WINDOWS - PICTURE UNITS

WH1P

R.O. (mm)	38 1/4" (972)	54 1/4" (1378)	62 1/4" (1581)	70 1/4" (1784)
F.S. (mm)	37 1/4" (948)	53 1/4" (1354)	61 1/4" (1557)	69 1/4" (1760)
V.G. (mm)	30 1/2" (775)	46 1/2" (1181)	54 1/2" (1384)	62 1/2" (1587)

37 3/8" (949)	41 1/8" (1051)	45 3/8" (1152)	49 3/8" (1254)	53 3/8" (1356)	57 3/8" (1457)	61 3/8" (1559)	65 3/8" (1661)	69 3/8" (1762)	73 3/8" (1864)	77 3/8" (1965)	81 3/8" (2067)
37 7/8" (937)	40 7/8" (1038)	44 7/8" (1140)	48 7/8" (1241)	52 7/8" (1343)	56 7/8" (1445)	60 7/8" (1546)	64 7/8" (1648)	68 7/8" (1749)	72 7/8" (1851)	76 7/8" (1953)	80 7/8" (2054)
32 5/8" (830)	32 5/8" (830)	36 5/8" (932)	40 5/8" (1033)	44 5/8" (1135)	48 5/8" (1236)	52 5/8" (1338)	56 5/8" (1440)	60 5/8" (1541)	64 5/8" (1643)	68 5/8" (1744)	72 5/8" (1846)
3230	4830	5630	6430	3234	4834	5634	6434	3238	4838	5638	6438
3242	4842	5642	6442	3246	4846	5646	6446	3250	4850	5650	6450
3254	4854	5654	6454	3258	4858	5658	6458	3262	4862	5662	6462
3266	4866	5666	6466	3270	4870	5670	6470	3274	4874	5674	6474

* Please visit our web site for the energy performance of these products at www.lepagemilwork.com

Custom sizes are available on request. Minimum and maximum sizes applicable may vary depending on features and options.
 For masonry openings, please contact your local Lepage representative.
 Lite patterns shown are 7/8" (22) SDL. Lite patterns for 5/8" (16) SDL, 1 1/4" (31) SDL and other grilles may vary.
 Grille configurations shown have been designed for grilles to align with standard double hungs.
 Some restrictions concerning SDL spacer bar availability may apply to glass surfaces larger than 30 sq. ft.

R.O.: Rough Opening
 F.S.: Frame Size
 V.G.: Visible Glass