



Manu Data

Hung Window H-100 – Aluminum Clad

Frame:

- Pine, red grandis or mahogany
- Aluminum clad, extruded 0.060", 1.5mm thick
- Thickness 1 7/16" (36mm)
- Depth 4 9/16" (116mm)

Sash:

- Pine, red grandis or mahogany
- Aluminum clad, extruded 0.060", 1.5mm thick
- Thickness 1 3/4" (44,5mm) standard

Interior finish:

- Natural, primed, first coat, Lepage stain or paint over 50 colors

Exterior finish:

- Lepage paint over 50 colors

Hardware:

- Recessed, white coppertone, polish brass, oil rubbed bronze, satin nickel, satin chrome
- Surface mount: unlaquered brass, polish brass, polish nickel, oil rubbed bronze, satin nickel

Weather-strip

- Q-Ion and silicone

Insulated glass:

- Double glaze 3/4" (19 mm)
- "Technoform" spacer, bronze, white, black or grey.
- Argon

Glass available:

- Clear, grey, bronze, pinhead, glue-chip
- Low-e: Energy advantage, 272, 366, 189
- Tempered
- Laminated

Screen:

- Mesh: invisible fiberglass, grey or black aluminium
- Aluminium surround Lepage paint over 50 colors
- Retractable

Grilles:

- Removable 7/8"
- Internal georgian 3/4", 1" or 1 3/4"
- Internal flat 5/16", 5/8", 3/4" or 1"
- Internal tubular: white, brass or pewter

Simulated Divided Lites (SDL):

- 5/8", 7/8", 1 1/4" or 1 3/4"
- Spacer bars bronze, grey, white or black

Casing:

- 908
- 2 3/4" Flat casing
- 3 1/2" Flat casing
- 3 15/16" Backbend (D-090)
- Nailing fin

Sill Extension:

- Standard D-082 (1" x 1 1/4")
- Historic D-083 (1 3/4" x 2")

Interior Jamb Extension:

- Finish and wood species same as interior frame 1/8" min and 6" max

Minimums and Maximums

Minimum width:	13 1/2"	Maximum width:	48"
Minimum height:	24"	Maximum height:	84"

Framing size, maximum: 23.1 sq. ft. (9 sq. ft. I.G.) (3mm glass) (operating sash)
 19 sq. ft. (7 sq. ft. I.G.) (4mm glass) (operating sash)

For more information, please visit our web site at www.lepagemillwork.com